

Electromagnetic Thickness Gauge DE-2000



Features:

- No need of couplant
- workpiece surface temperature less than 600°C depending on transducers
- The larger colorful TFT display 320×240
- High precision
- Suitable only for metal, such as steel pipe walls, flat steel, rods, or other products made of metal, even rust or corrosion on the surface
- Not sensitive to coating on the surface, so thickness of workpiece with coating could be tested
- Suitable for different shapes of metal, such as small pipe, elbow pipe and so on
- Widely application in Petrochemical industry, Metallurgy, Ship-building, Wind power, Nuclear electric power, Aerospace and so on
- Large memory of 10, 000 data; data transfer with software free
- Auto power off for saving battery power

Technical Specification:

Measuring range	1.5-300mm
Resolution	0.01mm
Accuracy	$\pm 0.04\text{mm}$ ($H < 9.99\text{mm}$)
	$\pm (0.1\%H + 0.04)\text{mm}$ $10 \leq H < 100\text{mm}$
	$\pm 0.3\%H$ $H > 100\text{mm}$
Temperature range	-15—600℃
Gain	Auto and Manual
Scan mode	A and B Scan
Excitation mode	Permanent magnet
Transducer	Anti-impact, stand wear and tear
Transducer classification	Normal or high temperature transducer
Memory	10,000 data
Output	USB, software free
Display	320×240 color display
Power	Li battery
Temperature	-20℃～+50℃
Dimension	181mm×93mm×29mm
Weight	0.4Kg (Battery included)

Standard Delivery:

- Main unit
- Transducer D035E
- Calibration block
- USB cable
- Carrying case
- Operating manual
- Calibration certificate

Manufactured by :Beijing Dragon Electronics Co.

Add:R.108 Building 38, Baiwang-Jasmine Garden, Haidian District, Beijing 100094 China
T: 86-10-62335745 F: 86-10-62314006 www.dgc-ndt.com.cn M: export2@dgc-ndt.com.cn